



## WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 1 of 14

### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT NAME

WIA ABRASOCORD 43

#### SYNONYMS

AC4332, AC4332M, AC4340, AC4350, "Welding Industries", W.I.A., FCAW, "welding electrode", "hard-surfacing and rebuilding rod", "self-shielded chrome-carbide hard-facing wire", 2465-A4, alloy


#### PRODUCT USE

Consumable, self shielded, hard facing electrode depositing a wear resistant alloy containing complex carbides. Non- machinable but grindable, prone to fine relief checking, limit to 3 layers build.

#### SUPPLIER

Company: Welding Industries Of Australia  
Address:  
5 Allen Street  
Melrose Park  
SA, 5039  
AUS  
Telephone: +61 8 8276 6494  
Telephone: 1300 300 884  
Fax: 1300 301 884


#### HAZARD RATINGS



### Section 2 - HAZARDS IDENTIFICATION

#### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.** According to the  
Criteria of NOHSC, and the ADG Code.



# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 2 of 14  
Section 2 - HAZARDS IDENTIFICATION

## POISONS SCHEDULE

None

## RISK

Causes burns.  
Risk of serious damage to eyes.  
Ingestion may produce health damage\*.  
Cumulative effects may result following exposure\*.  
Limited evidence of a carcinogenic effect\*.  
Possible respiratory sensitiser\*.  
\* (limited evidence).

## SAFETY

Wear eye/face protection.  
Take off immediately all contaminated clothing.  
In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
hard-facing electrode which in use generates welding fumes as iron oxide fume fluoride fume chromium fume manganese fume silica welding fumes and fumes of calcium oxide niobium oxides action of arc may generate ozone nitrogen oxides	Not avail. 1309-37-1 16984-48-8 7440-47-3 7439-96-5 69012-64-2 1305-78-8 10028-15-6 Mixture	 30-60 1-10 10-30 1-10 1-10 10-30 <3

## Section 4 - FIRST AID MEASURES

### SWALLOWED

Not normally a hazard due to the physical form of product. The material is a physical irritant to the gastro-intestinal tract.

### EYE

- Particulate bodies from welding spatter may be removed carefully.
- DO NOT attempt to remove particles attached to or embedded in eye.
- Lay victim down, on stretcher if available and pad BOTH eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye.
- Seek urgent medical assistance, or transport to hospital.

### SKIN

- If skin or hair contact occurs:
- Flush skin and hair with running water (and soap if available).
  - Seek medical attention in event of irritation.

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 3 of 14  
Section 4 - FIRST AID MEASURES

## INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

## NOTES TO PHYSICIAN

Copper, magnesium, aluminium, antimony, iron, manganese, nickel, zinc (and their compounds) in welding, brazing, galvanising or smelting operations all give rise to thermally produced particulates of smaller dimension than may be produced if the metals are divided mechanically. Where insufficient ventilation or respiratory protection is available these particulates may produce "metal fume fever" in workers from an acute or long term exposure.

- Onset occurs in 4-6 hours generally on the evening following exposure. Tolerance develops in workers but may be lost over the weekend. (Monday Morning Fever)

• Pulmonary function tests may indicate reduced lung volumes, small airway obstruction and decreased carbon monoxide diffusing capacity but these abnormalities resolve after several months.

• Although mildly elevated urinary levels of heavy metal may occur they do not correlate with clinical effects.

• The general approach to treatment is recognition of the disease, supportive care and prevention of exposure.

• Seriously symptomatic patients should receive chest x-rays, have arterial blood gases determined and be observed for the development of tracheobronchitis and pulmonary edema.

[Ellenhorn and Barceloux: Medical Toxicology].

• Acute chronic acid ingestion causes acute gastroenteritis, hepatic necrosis, bleeding and acute tubular necrosis with renal failure. The efficacy of British Anti-Lewisite haemodialysis and exchange transfusion has not been established.

• Primary irritation, including chrome ulceration, may be treated with ointments comprising calcium-sodium-EDTA. This, together with the use of frequently renewed dressings, will ensure rapid healing of any ulcer which may develop. The mechanism of action involves the reduction of Cr (VI) or Cr (III) and subsequent chelation; the irritant effect of Cr (III) / protein complexes is thus avoided.

[ILO Encyclopedia]

## BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Sampling time	Index	Comments
Total chromium in urine	Increase during shift	(10ug/g creatinine)	(B)
"	End of shift at end of workweek	(30ug/g creatinine)	(B)

B: Background levels occur in specimens collected from subjects NOT exposed.

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 4 of 14

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

### FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk, however containers may burn.
- In a fire may decompose on heating and produce toxic / corrosive fumes.

### FIRE INCOMPATIBILITY

None known.

### HAZCHEM

None

### Personal Protective Equipment

Gas tight chemical resistant suit.  
Limit exposure duration to 1 BA set 30 mins.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### EMERGENCY PROCEDURES

#### MINOR SPILLS

Clean up all spills immediately.  
Wear impervious gloves and safety glasses.  
Use dry clean up procedures and avoid generating dust.  
Place in suitable containers for disposal.

#### MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment if risk of overexposure exists.
- Prevent, by any means available, spillage from entering drains or water courses.
- Contain spill/secure load if safe to do so.
- Bundle/collect recoverable product and label for recycling.
- Collect remaining product and place in appropriate containers for disposal.
- Clean up/sweep up area. Water may be required.
- If contamination of drains or waterways occurs, advise emergency services.

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 5 of 14  
Section 6 - ACCIDENTAL RELEASE MEASURES

## EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

iron oxide fume	500 mg/m <sup>3</sup>
fluoride fume	250 mg/m <sup>3</sup>
chromium fume	250 mg/m <sup>3</sup>
manganese fume	500 mg/m <sup>3</sup>
silica welding fumes	50 mg/m <sup>3</sup>
calcium oxide	25 mg/m <sup>3</sup>

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

iron oxide fume	25 mg/m <sup>3</sup>
fluoride fume	2.5 mg/m <sup>3</sup>
chromium fume	2.5 mg/m <sup>3</sup>
manganese fume	5 mg/m <sup>3</sup>
silica welding fumes	10 mg/m <sup>3</sup>
calcium oxide	5 mg/m <sup>3</sup>

other than mild, transient adverse effects without perceiving a clearly defined odour is:

iron oxide fume	15 mg/m <sup>3</sup>
fluoride fume	2.5 mg/m <sup>3</sup>
chromium fume	1.5 mg/m <sup>3</sup>
manganese fume	3 mg/m <sup>3</sup>
silica welding fumes	6 mg/m <sup>3</sup>
calcium oxide	5 mg/m <sup>3</sup>

The threshold concentration below which most people will experience no appreciable risk of health effects:

iron oxide fume	10 mg/m <sup>3</sup>
fluoride fume	2.5 mg/m <sup>3</sup>
chromium fume	1 mg/m <sup>3</sup>
manganese fume	0.2 mg/m <sup>3</sup>
silica welding fumes	2 mg/m <sup>3</sup>
calcium oxide	5 mg/m <sup>3</sup>

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ + + + + +

+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 6 of 14

## Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

Earth all lines and equipment.

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### SUITABLE CONTAINER

Packaging as recommended by manufacturer.

- Check that containers are clearly labelled.

### STORAGE INCOMPATIBILITY

Keep dry.

Welding electrodes should not be allowed to come into contact with strong acids or other substances which are corrosive to metals.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL m5/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>
Australia Exposure Standards	iron oxide fume		5				
Australia Exposure Standards	iron oxide fume		10				
Australia Exposure Standards	fluoride fume		2.5				
Australia Exposure Standards	chromium fume		0.5				
Australia Exposure Standards	chromium fume		0.5				
Australia Exposure Standards	manganese fume		1		3		

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
 Issue Date: 30-Mar-2006  
 C317SC

CHEMWATCH 50525  
 CD 2006/2 Page 7 of 14

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL m5/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>
Australia Exposure Standards	manganese fume		1				
Australia Exposure Standards	calcium oxide		2				
Australia Exposure Standards	ozone					0.1	0.2

The following materials had no OELs on our record under the following CAS or Chemwatch (CW) numbers  
 WIA Abrasocord 43: No data available for CW:50525  
 welding fumes: No data available for CW:35201  
 fluoride fume: No data available for CAS:16984-48-8  
 manganese fume: No data available for CAS:7439-96-5  
 silica welding fumes: No data available for CAS:69012-64-2  
 nitrogen oxides: No data available for  
 Mixture: No data available for

### EMERGENCY EXPOSURE LIMITS

Material	Original IDLH Value (ppm)	Original IDLH Value (mg/m <sup>3</sup> )	Revised IDLH Value (mg/m <sup>3</sup> )	Revised IDLH Value (ppm)
iron oxide fume	N.E.	N.E.	2,500	
chromium fume	N.E.	N.E.	250	
manganese fume	N.E.	N.E.	500	
calcium oxide	Unknown	Unknown	25	
ozone	10			5

None assigned. Refer to individual constituents.

### INGREDIENT DATA

#### WELDING FUMES:

In addition to complying with any individual exposure standards for specific contaminants, where current manual welding processes are used, the fume concentration inside the welder's helmet should not exceed 5 mg/m<sup>3</sup>, when collected in accordance with the appropriate standard (AS 3640, for example).

ES\* TWA: 5 mg/m<sup>3</sup>

TLV\* TWA: 5 mg/m<sup>3</sup>, B2 (a substance of variable composition)

OES\* TWA: 5 mg/m<sup>3</sup>

Most welding, even with primitive ventilation, does not produce exposures inside the welding helmet above 5 mg/m<sup>3</sup>. That which does should be controlled (ACGIH).

Inspirable dust concentrations in a workers breathing zone shall be collected and measured in accordance with AS 3640, for example. Metal content can be analytically determined by OSHA Method ID25 (ICP-AES) after total digestion of filters and dissolution of captured metals. Sampling of the Respirable Dust fraction requires cyclone separator devices (elutriators) and procedures to comply with AS 2985 (for example).

#### IRON OXIDE FUME:

ES\* TWA: 5 mg/m<sup>3</sup> (as Fe in fumes and gases from welding and cutting)

TLV\* TWA: 5 mg/m<sup>3</sup> (as Fe) A4

NOTE: This substance has been classified by the ACGIH as A4 NOT classifiable as causing Cancer in humans.

OES\* TWA: 5 mg/m<sup>3</sup>; STEL: 10 mg/m<sup>3</sup> (as Fe)

#### FLUORIDE FUME:

TLV\* TWA: 2.5 mg/m<sup>3</sup>

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 8 of 14

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ES\* TWA: 2.5 mg/m<sup>3</sup>  
OES\* TWA: 2.5 mg/m<sup>3</sup>  
IDLH Level: 500 mg/m<sup>3</sup>

### CHROMIUM FUME:

as dust and fume:  
TLV\* TWA: 0.5 mg/m<sup>3</sup>  
ES\* TWA: 0.5 mg/m<sup>3</sup>

### MANGANESE FUME:

ES\* TWA: 1 mg/m<sup>3</sup> STEL: 3 mg/m<sup>3</sup>  
OES\* TWA: 1 mg/m<sup>3</sup>; STEL: 3 mg/m<sup>3</sup> (as Mn)

### SILICA WELDING FUMES:

Not available. Refer to individual constituents.

### CALCIUM OXIDE:

The TLV-TWA is thought to be protective against undue irritation and is analogous to that recommended for sodium hydroxide.

### OZONE:

NOTE: Detector tubes for ozone, measuring in excess of 0.05 ppm, are commercially available.

Exposure at 0.2 ppm appears to produce mild acute but not cumulative effects. It is thought that exposures of the order of 0.1 ppm will be tolerated by most workers including asthmatics. Chronic exposure at 0.1 ppm or more can induce significant adverse effects in the lower respiratory tract of both normal and atopic individuals.

Human exposure for 2 hours at an average concentration of 1.5 ppm ozone resulted in a 20% reduction in timed vital capacity of the lung and other effects. Concentrations of ozone in excess of a few tenths ppm cause occasional discomfort to exposed individuals manifest as headache, dryness of the throat and mucous membranes of the eyes and nose following exposures of short duration.

Exposure to ozone during moderate to heavy work loads results in significantly decreased forced vital capacity (FVC) and forced expiratory volume in one second (FEV1) at 0.12 ppm; this effect is greater at higher concentrations.

### NITROGEN OXIDES:

Data for nitrogen dioxide:

TLV TWA: 3 ppm 6 mg/m<sup>3</sup> STEL: 5 ppm 10 mg/m<sup>3</sup>  
ES TWA: 3 ppm 5.6 mg/m<sup>3</sup> STEL: 5 ppm 9.4 mg/m<sup>3</sup>

IDLH Level: 50 ppm

NOTE: Detector tubes for nitrogen dioxide, measuring in excess of 0.5 ppm, are commercially available.

## PERSONAL PROTECTION



### EYE

Welding helmet with suitable filter. Welding hand shield with suitable filter.

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 9 of 14

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

• Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].  
For most open welding/brazing operations, goggles, even with appropriate filters, will not afford sufficient facial protection for operators. Where possible use welding helmets or handshields corresponding to AS 1336 and AS 1338 which provide the maximum possible facial protection from flying particles and fragments. [WRIA-WTIA Technical Note 7].

### HANDS/FEET

Welding Gloves  
Safety footwear.

### OTHER

Overalls.  
• Eyewash unit.  
Aprons, sleeves, shoulder covers, leggings or spats of pliable flame resistant leather or other suitable materials may also be required in positions where these areas of the body will encounter hot metal.

### ENGINEERING CONTROLS

Special ventilation requirements apply for processes which result in the generation of barium, chromium, lead, or nickel fume and in those processes which generate ozone.  
The use of mechanical ventilation by local exhaust systems is required as a minimum in all circumstances (including outdoor work). (In confined spaces always check that oxygen has not been depleted by excessive rusting of steel or snowflake corrosion of aluminium)  
Local exhaust systems must be designed to provide a minimum capture velocity at the fume source, away from the worker, of 0.5 metre/sec. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:  
welding " brazing fumes (released at relatively low velocity into moderately still air)

Air Speed:  
0.5-1.0 m/s (100-200 f/min.)

Within each range the appropriate value depends on:

Lower end of the range  
1: Room air currents minimal or favourable to capture  
2: Contaminants of low toxicity or of nuisance value only.  
3: Intermittent, low production.  
4: Large hood or large air mass in motion

Upper end of the range  
1: Disturbing room air currents  
2: Contaminants of high toxicity  
3: High production, heavy use  
4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 10 of 14

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of welding or brazing fumes generated 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

If risk of inhalation or overexposure exists, wear SAA approved respirator or work in fume hood.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Black coloured, flux coated wire electrode. Plain tip. Cold electrode wire is odourless. Insoluble in water.

Weld deposit: 5.0%C, 0.7%Mn, 22.0%Cr, 7.0%Nb balance Fe.

Multi-layer hardness 64-69 HRC.

### PHYSICAL PROPERTIES

Does not mix with water.

Sinks in water.

Acid.

Molecular Weight: Not applicable

Melting Range (°C): >1500

Solubility in water (g/L): Immiscible

pH (1% solution): Not applicable.

Volatile Component (%vol): Not applicable

Relative Vapour Density (air=1): Not applicable

Lower Explosive Limit (%): Not applicable

Autoignition Temp (°C): Not applicable

State: Manufactured

Boiling Range (°C): Not applicable

Specific Gravity (water=1): >6

pH (as supplied): Not applicable

Vapour Pressure (kPa): Not applicable

Evaporation Rate: Not applicable

Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not applicable

Decomposition Temp (°C): Not available.

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

### CONDITIONS CONTRIBUTING TO INSTABILITY

Product is considered stable and hazardous polymerisation will not occur.

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments.

##### EYE

Fumes from welding/brazing operations may be irritating to the eyes.

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 11 of 14

## Section 11 - TOXICOLOGICAL INFORMATION

### SKIN

Chrome fume, as the chrome VI oxide, is corrosive to the skin and may aggravate pre-existing skin conditions such as dermatitis and eczema. As a potential skin sensitiser, the fume may cause dermatoses to appear suddenly and without warning. Absorption of chrome VI compounds through the skin can cause systemic poisoning affecting the kidneys and liver.

### INHALED

Chrome fume is irritating to the respiratory tract and lungs. Toxic effects result from over-exposure. Asthmatic conditions may result as a consequence of the sensitising action of chrome VI compounds.

Fluoride vapours and thermally produced particulates (fume) of the calcium, sodium and potassium salts are potent mucous membrane irritants.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

### CHRONIC HEALTH EFFECTS

Principal route of exposure is inhalation of welding fumes from electrodes and workpiece. Reaction products arising from electrode core and flux appear as welding fume depending on welding conditions, relative volatilities of metal oxides and any coatings on the workpiece. Studies of lung cancer among welders indicate that they may experience a 30-40% increased risk compared to the general population. Since smoking and exposure to other cancer-causing agents, such as asbestos fibre, may influence these results, it is not clear whether welding, in fact, represents a significant lung cancer risk. Whilst mild steel welding represents little risk, the stainless steel welder, exposed to chromium and nickel fume, may be at risk and it is this factor which may account for the overall increase in lung cancer incidence among welders. Cold isolated electrodes are relatively harmless. Welding fume with high levels of ferrous materials may lead to particle deposition in the lungs (siderosis) after long exposure. This clears up when exposure stops. Chronic exposure to iron dusts may lead to eye disorders. Extended exposure to inorganic fluorides causes fluorosis, which includes signs of joint pain and stiffness, tooth discolouration, nausea and vomiting, loss of appetite, diarrhoea or constipation, weight loss, anaemia, weakness and general unwellness. There may also be frequent urination and thirst. Redness, itchiness and allergy-like inflammation of the skin and mouth cavity can occur. The central nervous system may be involved. Exposure to fume containing high concentrations of water-soluble chromium (VI) during the welding of stainless steels in confined spaces has been reported to result in chronic chrome intoxication, dermatitis and asthma. Certain insoluble chromium (VI) compounds have been named as carcinogens (by the ACGIH) in other work environments. Chromium may also appear in welding fumes as Cr<sub>2</sub>O<sub>3</sub> or double oxides with iron. These chromium (III) compounds are generally biologically inert. Other welding process exposures can arise from radiant energy UV flash burns, thermal burns or electric shock. The welding arc emits ultraviolet radiation at wavelengths that have the potential to produce skin tumours in animals and in over-exposed individuals, however, no confirmatory studies of this effect in welders have been reported.

### TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

MATERIAL	CARCINOGEN	SENSITISER	SKIN	REPROTOXIN
iron oxide fume	IARC:Group 3: Not classifiable as to "carcinogenic"			

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet

Issue Date: 30-Mar-2006

C317SC

CHEMWATCH 50525

CD 2006/2 Page 12 of 14

Section 11 - TOXICOLOGICAL INFORMATION

chromium fume  
ity" to  
humans  
IARC:Group  
3: Not  
classifiable  
as to  
"carcinogenic  
ity" to  
humans

manganese fume

ILOM ILOEI

## CARCINOGEN

IARC: International Agency for Research on Cancer (IARC)

Carcinogens: iron oxide fume Category: Group 3: Not classifiable

as to carcinogenicity to humans

## CARCINOGEN

IARC: International Agency for Research on Cancer (IARC)

Carcinogens: chromium fume Category: Group 3: Not classifiable as

to carcinogenicity to humans

## REPROTOXIN

ILOM: ILO Agents toxic to the male reproductive system: manganese fume

## REPROTOXIN

ILOEI: ILO Chemicals in the electronics industry that have toxic effects on reproduction: manganese fume

## Section 12 - ECOLOGICAL INFORMATION

No data.

Refer to data for ingredients, which follows:

SILICA WELDING FUMES:

No data

OZONE:

The material is classified as an ecotoxin\* because the Fish LC50 (96 hours) is less than or equal to 0.1 mg/l

\* Classification of Substances as Ecotoxic (Dangerous to the Environment)

Appendix 8, Table 1

Compiler's Guide for the Preparation of International Chemical Safety Cards: 1993 Commission of the European Communities.

## Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

## Section 14 - TRANSPORTATION INFORMATION

HAZCHEM

None

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet  
Issue Date: 30-Mar-2006  
C317SC

CHEMWATCH 50525  
CD 2006/2 Page 13 of 14  
Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN,IATA,IMDG

## Section 15 - REGULATORY INFORMATION

### POISONS SCHEDULE

None

### REGULATIONS

welding fumes (CAS No:Not avail):  
No regulations applicable

iron oxide fume (CAS: 1309-37-1) is found on the following regulatory lists;  
Australia High Volume Industrial Chemical List (HVICL)  
Australia Inventory of Chemical Substances (AICS)  
International Agency for Research on Cancer (IARC) Carcinogens  
International Council of Chemical Associations (ICCA) - High Production Volume List  
OECD Representative List of High Production Volume (HPV) Chemicals

fluoride fume (CAS: 16984-48-8) is found on the following regulatory lists;  
Australia Poisons Schedule

chromium fume (CAS: 7440-47-3) is found on the following regulatory lists;  
Australia - Western Australia Hazardous Substances Prohibited for Specified Uses or Methods of Handling  
Australia Inventory of Chemical Substances (AICS)  
International Agency for Research on Cancer (IARC) Carcinogens  
OECD Representative List of High Production Volume (HPV) Chemicals

manganese fume (CAS: 7439-96-5) is found on the following regulatory lists;  
Australia Inventory of Chemical Substances (AICS)  
OECD Representative List of High Production Volume (HPV) Chemicals

silica welding fumes (CAS: 69012-64-2) is found on the following regulatory lists;  
Australia Inventory of Chemical Substances (AICS)  
OECD Representative List of High Production Volume (HPV) Chemicals

calcium oxide (CAS: 1305-78-8) is found on the following regulatory lists;  
Australia High Volume Industrial Chemical List (HVICL)  
Australia Inventory of Chemical Substances (AICS)  
International Council of Chemical Associations (ICCA) - High Production Volume List  
OECD Representative List of High Production Volume (HPV) Chemicals

No data available for welding fumes as CAS: Not avail.  
No data available for ozone as CAS: 10028-15-6.  
No data available for nitrogen oxides as CAS: Mixture.

## Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from

continued...

# WIA ABRASOCORD 43

Chemwatch Material Safety Data Sheet

Issue Date: 30-Mar-2006

C317SC

CHEMWATCH 50525

CD 2006/2 Page 14 of 14

Section 16 - OTHER INFORMATION

---

CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 30-Mar-2006

Print Date: 10-Jul-2006