

Dynasty 350DX

Part No: MR907204021



EXCEPTIONALLY SMOOTH & PRECISE ARC.

FAN-ON-DEMAND™

Power source cooling system operates only when needed - reducing noise, energy use and the amount of contaminants pulled through the machine.

LIFT-ARC™ STARTING

Provides X-Ray clean welds without the use of high frequency.

BLUE LIGHTNING™

High-frequency arc starter for non-contact arc initiation. Provides more consistent arc starts and greater reliability.

METER CALIBRATION

Allows meters to be calibrated for certification.

WIND TUNNEL TECHNOLOGY™

Protects internal electrical components from airborne contaminants, extending the product life.

PROGRAM MEMORY

► Features 9 independent program memories that maintain/save your parameters.

AUTO-POSTFLOW

Calculates the length of postflow time based on the Amperage setting.

► This eliminates the need to independently set the postflow time for different Amperages.

► This feature preserves your tungsten and prevents porosity.

VRD TO CAT C AS 1674.2

3 YEAR WARRANTY

For details, refer to Miller's True Blue warranty statement.

APPLICATIONS

Precision Fabrication
Heavy Fabrication
Pipe and Tube Fabrication
Aluminium Ship Repair
Anodized Aluminium Fabrication

PROCESSES

TIG (GTAW)
Pulsed TIG (GTAW-P)
Stick (SMAW)



AMP RANGE	RATED OUTPUT	AMPS INPUT AT RATED OUTPUT, 50/60 HZ		DIMENSIONS (MM)	WEIGHT
		400 V	KVA		
3 - 350 A	250 A at 30 V, 100% Duty Cycle	15 A	10.3	H: 629	61kg
	300 A at 32 V, 60% Duty Cycle	18 A	12.7	W: 349 D: 559	