



WIREFEEDER W67

P/N: WFL019

4 Roll Drive
Wire Feeder.
For Consistent
Wire Feed Control.











WIREFEEDER W67





P/N: WFL019

4 Roll Drive Wire Feeder. For Consistent Wire Feed Control.

Suitable for the Weldmatic 350 and 500, the W67 wire feeder provides the ultimate wire feeding capabilities. The 4 roll drive motor produces a consistent and strong drive for a variety of wires, while the digital meters provide finer set up and control.

With added features including Arc start, purge, latch, burn back and more, the W67 gives users the versatility to custom their settings to suit their wire feeding needs and preferences. Built with heavy duty quality components, and manufactured with 3 years warranty, the W67 offers reliability and performance that's second to none.



SPECIFICATIONS

Primary Voltage	Rated Primary Current	Spool Sizes	Wire Speed Range
24 V DC (from welding power source)	5 Amps	5kg & 15kg	17-189 RPM: 2-22 m/min
Wire Size Range	Pre/Post Gas	Spot Time	Arc Start
0.9mm - 1.6 mm	Yes, 0-10 seconds	Yes, 0-10 seconds	Soft/Fast
Latch	Weight	Warranty	
2T/4T Modes	15.2kg	3 Vears	

FEATURES

- Suits 5 and 15kg spools
- Heavy Duty 4 Roll Drive Large strong drive gears and ball bearings
- Arc Start Control Fine tunes starting response to suit weld conditions
- Purge Purges gas line without feeding wire
- Inch Feeds wire without wasting gas
- Latch Stop / Start gun switch trigger.
 Reduces operator fatigue
- Pre Gas Allows gas to flow before weld starts
- Post Gas Continued gas flow after weld has finished
- Spot time For short weld times for repetitive spot welds
- Burn back Controls wire burn back upon weld completion

BEST USED WITH

Product	Part Number	
Austfil T-11 Self-Shielded Flux-Cored Wire	AUST11085KG (0.8mm – 5kg Spool) AUST11095KG (0.9mm – 5 kg Spool) AUST11125kg (1.2mm – 5kg Spool)	
Austmig ES6 Mild Steel Wire	ES606M5KG (0.6mm – 5kg Spool) ES608M5KG (0.8mm – 5kg Spool) ES609M5KG (0.9mm – 5kg Spool)	
Austmig 5356 Aluminium Wire	M5356092KG (0.9mm – 2kg Spool) M5356102KG (1.0mm - 2kg Spool) M5356122KG (1.2mm - 2kg Spool)	
Austfil Excel Gas Shielded Flux Cored Wire	AE71CM12 (1.2.mm – 15kg Spool) AE71CM16 (1.6.mm – 15kg Spool)	
WIA OpticFX Helmet	SH300001 (Nero) SH300002 (Blue Knight)	